

aselsan

Professional Communications
Repeater Family

PROFESSIONAL COMMUNICATIONS REPEATER FAMILY

4700 FIXED TYPE



4700 MODULAR MOBILE



4700 COMPACT MOBILE



4900 FIXED TYPE



4900 MOBILE



4700 Fixed Type Repeater

General Features

- Modular Design
- 19" Rack Structure
- Duplex Communication
- Adjustable RF Output Power
- Ethernet/IP Interface
- Continuous Duty
- Capability of being supplied by an accumulator (in case of electricity outage)
- Built-in Self Test and Alarm Indication
- Support of Analog, DMR and P25 Systems (with required software changes)
- Full Compatibility with ETSI 300-086 (Analog), ETSI 300-113 (Digital:DMR) and TIA-102.CAAB-D (Digital:P25) standards

Digital Features

- Repetition of Base Band Signal without Decryption
- Regeneration of Digital Voice & Data with Error Detection and Error Correction Algorithms
- Digital Modulation: 4FSK (DMR), C4FM (P25)



General Technical Specifications

Frequency Range	VHF: 136-174 MHz (D/R 4741) UHF: 380-470 MHz (D/R 4745)
Channel Separation	12.5 kHz (DMR or P25) 25 kHz (Analog)
Number Of Channels	99 (Programmable)
RF Output Power	VHF: 10-90 W UHF: 10-70 W
Modulation	FM (Analog), 4FSK (DMR), C4FM (P25)
Operating Voltage	13.6Vdc \pm 20%
Standby Current	\leq 700 mA @ 13.6 Vdc
Operating Current	\leq 20 A @ 13.6 Vdc
Dimensions (HxWxL)	\approx 133x482x361 mm (without accessories)
Weight	\approx 10.5 kg (without accessories)
Operating Temperature	-30 °C / +60 °C
Storage Temperature	-40 °C / +85 °C
Humidity	90 % @ 50 °C

Receiver Technical Specifications*

Analog Sensitivity	VHF : \leq -119 dBm (@ 12 dB SINAD) UHF : \leq -118 dBm (@ 12 dB SINAD)
Digital Sensitivity	DMR: VHF: \leq -117 dBm (@ 1% BER) UHF: \leq -116 dBm (@ 1% BER) P25: VHF: \leq -120 dBm (@ 1% BER) UHF: \leq -119 dBm (@ 1% BER)
Adjacent Channel Selectivity	\geq 60 dB (@ 12.5 kHz)
Co-Channel Rejection	\geq -12 dB (DMR) \leq 9 dB (P25)
Bit Error Rate Floor	\leq 0.01%
Receiver Audio Distortion	< 5% (@ 100 mW, 8 Ω)

Transmitter Technical Specifications*

RF Output Power	VHF: 10-90W / UHF: 10-70W
Adjacent Channel Power Ratio	>60 dB (@ 12.5 kHz)
Spurious Emissions	<-36 dBm (DMR) / <-20 dBm (P25)
Modulation Limiting	\pm 2.5 kHz (@ 12.5 kHz)
Frequency Stability	\leq 0.5 ppm

*According to ETSI Standards

4700 Modular Mobile Repeater

General Features

- Easily Transportable
- Rapid Deployment in Required Area
- Modular Design
- Duplex Communication
- Adjustable RF Output Power
- Continuous Duty
- Capability of Being Supplied by an Accumulator (In Case of Electricity Outage)
- Built-in Self Test and Alarm Indication
- Support of Analog, DMR and P25 Systems (with required software changes)
- Full Compatibility with ETSI 300-086 (Analog), ETSI 300-113 (Digital:DMR) and TIA-102.CAAB-D (Digital:P25) standards



Digital Features

- Repetition of Base Band Signal without Decryption
- Regeneration of Digital Voice & Data with Error Detection and Error Correction Algorithms
- Digital Modulation: 4FSK (DMR), C4FM (P25)



General Technical Specifications

Frequency Range	VHF: 136-174 MHz (D/R 4741) UHF: 380-470 MHz (D/R 4745)
Channel Separation	12.5 kHz (DMR or P25) 25 kHz (Analog)
Number Of Channels	99 (Programmable)
RF Output Power	VHF: 10-40 W UHF: 10-30 W
Modulation	FM (Analog), 4FSK (DMR), C4FM (P25)
Operating Voltage	13.6Vdc ± 20 %
Standby Current	≤ 700 mA @ 13.6 Vdc
Operating Current	≤ 10 A @ 13.6 Vdc
Dimensions (HxWxL)	≈ 156x204x329 mm (without accessories)
Weight	≈ 8.5 kg (without accessories)
Operating Temperature	-30 °C / +60 °C
Storage Temperature	-40 °C / +85 °C
Humidity	90% @ 50 °C

Receiver Technical Specifications*

Analog Sensitivity	VHF: ≤ -119 dBm (@ 12 dB SINAD) UHF: ≤ -118 dBm (@ 12 dB SINAD)
Digital Sensitivity	DMR: VHF: ≤ -117 dBm (@ 1% BER) UHF: ≤ -116 dBm (@ 1% BER) P25: VHF: ≤ -120 dBm (@ 1% BER) UHF: ≤ -119 dBm (@ 1% BER)
Adjacent Channel Selectivity	≥ 60 dB (@ 12.5 kHz)
Co-Channel Rejection	≥ -12 dB (DMR) ≤ 9 dB (P25)
Bit Error Rate Floor	≤ 0.01%
Receiver Audio Distortion	< 5% (@ 100 mW, 8 Ω)

Transmitter Technical Specifications*

RF Output Power	VHF: 10-40W / UHF: 10-30W
Adjacent Channel Power Ratio	>60 dB (@ 12.5 kHz)
Spurious Emissions	<- 36 dBm (DMR) / <- 20 dBm (P25)
Modulation Limiting	± 2.5 kHz (@ 12.5 kHz)
Frequency Stability	≤ 0.5 ppm

*According to ETSI Standards

4700 Compact Mobile Repeater

General Features

- Easily Transportable
- Rapid Deployment in Required Area
- Compact Design
- Synthesized & Microprocessor Controlled
- Adjustable Output Power
- Continuous Duty
- Status & Alarm Indications
- Uninterruptable Battery Operation
- Full Compatibility with ETSI 300-086 (Analog) and TIA-102.CAAB-D (Digital:P25) Standards



Digital Features

- Repetition of Base Band Signal Without Decryption
- Regeneration of Digital Voice & Data with Error Detection and Error Correction Algorithms
- Digital Modulation: C4FM (P25)

Environmental Features

- ESD: IEC 801 - 2KV



General Technical Specifications

Frequency Range	VHF: 136-174 MHz (Full Band)
Channel Separation	12.5 kHz / 25kHz
Number Of Channels	99 (Preset)
RF Output Power	VHF: 10-40 W
Modulation	FM (Analog), C4FM (P25)
RF Input / Output Impedance	50 Ω
Working style	Continuous
Operating Voltage	13.6 Vdc \pm 20%
Standby Current	\leq 0,5A
Operating Current	\leq 8A
Operating Temperature	-30 $^{\circ}$ C / +60 $^{\circ}$ C
Storage Temperature	-40 $^{\circ}$ C / +85 $^{\circ}$ C
Humidity	90%, @50 $^{\circ}$ C (Relative Humidity)
Dimensions (HxWxL)	73x297x182 mm (without duplexer & accessories)
Weight	\leq 3.5 kg (without duplexer & accessories)

Receiver Technical Specifications

Sensitivity	\leq 0.35 μ V (ETSI 20 dB SINAD / 1 % BER) \leq 0.25 μ V (TIA 12 dB SINAD / 5 % BER)
Adjacent Channel Rejection	\geq 60 dB
Intermodulation Rejection	\geq 70 dB (ETSI) \geq 80 dB (TIA)
Spurious Reception Rejection	\geq 90 dB
Co-Channel Rejection	\leq 9 dB
Audio Output Power	100 mW / 8 Ω (at option connector)

Transmitter Technical Specifications

RF Output Power	10-40 W
Operating Frequency Accuracy (-30 $^{\circ}$ C / +60 $^{\circ}$ C; 25 $^{\circ}$ C ref)	\leq 1.5 ppm
Conducted Spurious Emissions	\leq -20 dBm
Symbol Rate Accuracy	\leq 10 ppm
Modulation Fidelity	RMS Error \leq 5% Deviation: 1800 \pm 10 Hz
Frequency Deviation	High: 2828 \pm 10 Hz Low: 943 \pm 10 Hz

Mobile Duplexer Specification

Attenuation	> 80 dB (One channel)
Insertion Loss	< 2.2 dB
Tx-Rx Separation	> 4 MHz

4900 Fixed Type Repeater Radio

General Features

- Physical Structure Providing Advantages In Terms of Weight and Dimensions
- VHF/UHF Dual Band Operation
- Support for Analog, DMR and P25 Systems without any Firmware Change
- Linux Operating System
- Capability of Changing the Operation Mode to Mobile Repeater or Terminal (with Simple Firmware and Hardware Changes)
- Duplex Communication
- Adjustable RF Output Power
- Continuous Duty
- Capability of Being Supplied by an Accumulator (In Case of Electricity Outage)
- Built-in Self Test
- Full Compatibility with ETSI 300-086 (Analog), ETSI 300-113 (Digital: DMR) and TIA-102.CAAB-D (Digital: P25) Standards

Digital Features

- Repetition of Base Band Signal without Decryption
- Regeneration of Digital Voice & Data with Error Detection and Error Correction Algorithms

Environmental Features

- MIL-STD-810C/D/E/F/G (Related method and procedures)



General Technical Specifications

Weight	2425 g
Dimensions	61x177x246 mm
Operating Temperature	-30 °C/+60 °C
Storage Temperature	-40 °C/+80 °C
Power Supply	13.6 Vdc \pm 20%
Processor	ARM9
Operating System	Linux

Receiver Technical Specifications

Frequency Range	136-174 MHz (VHF) 380-470 MHz (UHF)
Sensitivity	\leq -119 dBm (VHF) \leq -118 dBm (UHF)
Intermodulation Rejection	\geq 75 dB
Audio Distortion	\leq 5% (rated audio power) \leq 5% (17dB below rated audio power)
BER	\leq 0.01%
Stand-by Current- Reception (Rx) Current	\leq 500 mA, \leq 1.2 A

Transmitter Technical Specifications

Frequency Range	136-174 MHz (VHF) 380-470 MHz (UHF)
Dual Band Transmission Power Range	10-40 W (VHF) 10-30 W (UHF)
Single Band Transmission Power Range	10-90 W (VHF) 10-70 W (UHF)
Frequency Accuracy	\leq 0.5 ppm
Modulation Fidelity	\leq 3%
Transmission (Tx) Current	\leq 8.0 A

4900 Mobile Repeater Radio

General Features

- Easily Transportable
- Rapid Deployment in Required Area
- VHF/UHF Dual Band Operation
- Support for Analog, DMR and P25 Systems without any Firmware Change
- Linux Operating System
- Capability of Changing the Operation Mode to Fixed Type Repeater or Terminal (with Simple Firmware and Hardware Changes)
- Duplex Communication
- Adjustable RF Output Power
- Continuous Duty
- Capability of Being Supplied by an Accumulator (In Case of Electricity Outage)
- Built-in Self Test
- Full Compatibility with ETSI 300-086 (Analog), ETSI 300-113 (Digital: DMR) and TIA-102.CAAB-D (Digital: P25) Standards

Digital Features

- Repetition of Base Band Signal without Decryption
- Regeneration of Digital Voice & Data with Error Detection and Error Correction Algorithms

Environmental Features

- MIL-STD-810C/D/E/F/G (Related method and procedures)



General Technical Specifications

Weight	2425 g
Dimensions	61x177x246 mm
Operating Temperature	-30 °C/+60 °C
Storage Temperature	-40 °C/+80 °C
Power Supply	13.6 Vdc \pm 20%
Processor	ARM9
Operating System	Linux

Receiver Technical Specifications

Frequency Range	136-174 MHz (VHF) 380-470 MHz (UHF)
Sensitivity	\leq -119 dBm (VHF) \leq -118 dBm (UHF)
Intermodulation Rejection	\geq 75 dB
Audio Distortion	\leq 5% (rated audio power) \leq 5% (17dB below rated audio power)
BER	\leq 0.01%
Stand-by Current- Reception (Rx) Current	\leq 500 mA, \leq 1.2 A

Transmitter Technical Specifications

Frequency Range	136-174 MHz (VHF) 380-470 MHz (UHF)
Dual Band Transmission Power Range	10-40 W (VHF) 10-30 W (UHF)
Single Band Transmission Power Range	10-90 W (VHF) 10-70 W (UHF)
Frequency Accuracy	\leq 0.5 ppm
Modulation Fidelity	\leq 3%
Transmission (Tx) Current	\leq 8.0 A

Notes.....

A series of horizontal dotted lines for taking notes, starting from the first line below the 'Notes' header and continuing down the page.



aselsan



ASELSAN A.Ş. is a Turkish Armed Forces Foundation company.

aselsan

P: +90 (312) 592 10 00 F: +90 (312) 354 13 02
www.aselsan.com.tr | hbtmarketing@aselsan.com.tr